





### 3 1/2 & 4 1/2 DIGITAL CALIBRATOR mV / mA

#### COMMON SPECIFICATIONS



CAL - 400-3 / 4

Display	: 3 1/2 digit LCD	4 1/2 digit LCD
Range	: 200 mV / 20 mA	
Source	: 0 to 199.9 mV	0 to 199.99 mV
Output	: 0 to 19.99 mA	0 to 19.999 mA
Measure	: 0 to ± 199.9 mV	0 to ± 199.99 mV
Input	: 0 to ± 19.99 mA	0 to ± 19.999 mA
Accuracy	: 0.1% ± 2 Counts	0.05% ± 2 Counts
mA Load	: 500 E Max.	
Output Adjustable	: 10 turn POT Coarse & Fine	
Operating Temp.	: 0 to 50 °C (RH < 80%)	
Supply	: 9 V. DC. Battery (2 Nos.)	
Box	: Portable	
Includes	: Test Leads, Carrying Case & Thermocouple Tables	
Options	: Ac Adaptor 230 V. AC.	



CAL - 402-3 / 4

Display	: 3 1/2 digit Kinge Bright LED : 4 1/2 digit LCD		
Range	: 200 mV / μA	2 V / mA	20 V / mA
Source	: 0 to 199.9	0 to 1.999	0 to 19.99
Output	: 0 to 199.99	0 to 1.9999	0 to 19.999
Measure	: 0 to ± 199.9	0 to ± 1.999	0 to ± 19.99
Input	: 0 to ± 199.99	0 to ± 1.9999	0 to ± 19.999
Accuracy	: 3 1/2 - 0.1% ± 2 Counts, 4 1/2 - 0.05% ± 2 Counts		
mA Load	: 1 K E Max.		
Output Adjustable	: 10 turn POT Coarse & Fine		
Operating Temp.	: 0 to 50 °C (RH < 80%)		
Supply	: 230 V. AC. ± 10% 50 Hz		
Box	: Table Top		
Includes	: Test Leads, Thermocouple Tables		
Options	: 110 V. AC. Supply Voltage		

#### ORDERING CODE :

CAL - XXX - D

XXX (Supply)	D DIGIT
400 - 9 V.DC. (BAT)	3 - 3 1/2 199.9
402 - 230 V.AC.	4 - 4 1/2 199.99