




### RTD CALIBRATOR

#### COMMON SPECIFICATIONS



CAL 404 / 405



CAL 403 / 406

Fix Range	: -100, -50, -25, 000, +25, 50, 100, 150, 200, 250, 300, 400 °C for CAL-404 / CAL-403
Out Put	
12 Selectable	: -200, -100, -50, 000, 50, 100, 150, 200, 300, 400, 500, 600 °C for CAL-405 / CAL-406
Variable Range	
Output	: -200 °C to 600 °C for CAL - 403, CAL - 406
Accuracy	: ± 0.1% OHMS of FSR
Compensation	: LWC (Long Wire Compensation) Of 100 Meter sensor cable.
Include	: Test Leads, RTD Tables
Option	: 12 Selectable Ranges as per your requirement is possible.
Operating Temp.	: 0 to 50 °C (RH < 80%)
Supply	: Not required
Box Size	: Portable : 48 mm X 48 mm X 110 mm for CAL - 404 / CAL - 405 (HxWxD) : Table Top : 88 mm X 210 mm X 230 mm for CAL - 403 / CAL - 406

#### ORDERING CODE :

CAL - XXX		
XXX	(BOX)	RANGE
404	PORTABLE	- 100 to 400 °C
405		- 200 to 600 °C
403	TABLE TOP	- 100 to 400 °C
406		- 200 to 600 °C



Manufacturers:

### SHRIJI ELECTRONICS

7, Shivsagar Society, Krishna Nagar, Andheri Kuria Road,

Safed Pool, Pipe Line, Mumbai-400072.

Tel. : 022 2851 0847, 2851 1036, 2852 0149

Email : shriji\_ele@mtnl.net.in www.shrijielectronics.com

