




DIGITAL TIMER

COMMON SPECIFICATIONS



DT-301



DT-302

Display	: 0.5" ht 7 Segment LED
LED Indication	: a) Time Unit (Hrs. / Min / Sec.) b) Relay Status (Rly 1 / Rly 2) c) Auto Reset Time (RT)
Time Setting	: Through Push wheel Switches
Range	: 9.99, 99.9, 999 SEC 99.9, 999 MIN 99.9, 999 HRS. (user selectable)
Delay Modes	: ON Delay, OFF Delay (user selectable)
Reset	: a) Front Reset (programmable) b) Remote Reset (Via rear terminals) c) on power interruption (Programmable)
Reset Time	: < 100 ms
Time Accuracy	: 0.05% full scale
Repeat Accuracy	: 0.01%
Control Inputs	: a) Start b) Reset c) Hold
Memory retention	: Non - volatile (E ² prom) upto 10 Years
Output	: 6 Amp 2 c/o Relay 230 V. AC.
Operating Temp.	: 0 to 50 °C
Relative Humidity	: Below 95% RH (Non condensing)
Supply	: 90 to 270 V. AC, 50/60 Hz

Dimensions (H x W x D) mm	72 x 72 x 110	96 x 96 x 95	48 x 48 x 100
Panel Cutout (H x W) mm	68 x 68	92 x 92	45 x 45

ORDERING CODE :

DT - XXX

XXX	SIZE
301	72 X 72 mm
302	96 X 96 mm
303	48 X 48 mm